



























































## Installation Instructions:









## PRODUCT INFORM ATION

Style name / + P & th	渐变
Style name/产品名称	
Construction/结构	Multi-level Loop
Fiber/纤维	100% Nylon6
Dye method/染色工艺	100% solution dyed
Backing/底背	PVC
Tufting Gauge/针密	47.00 rows per 10cm
Pile Weight/绒重	560g/m <sup>2</sup>
Pile Height/绒高	5.5mm
Total Thickness/厚度	Approx 7mm
Tile Size/尺寸	250mmx1000mm
Nbs Smoke 烟密度	(ASTM E 662) less than 450
Flooring Radiant Panel 临界热辐射通量	Class I (Mean average CRF:0.45 watts/cm² orhigher) ASTM E-648
Electrostatic Propensity 静电倾向	3.0 kV or lower AATCC 134
Colourfastness to Light 耐光色牢度	≥4 after 100 hours AATCC 16E

## PRODUCT NOTES:

- 1. Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature, humidity and colour. Product specifications may vary within normal industry and standardised testing tolerances.
- 2. These specifications reflect mean averages based upon tests of production runs of this carpet style by independent laboratories. A range of variances is implicit in the testing process. Furthermore, the standard test methods established to derive the specifications lack a degree of precision and repeatability; therefore, individual test results on the actual carpet purchased may differ from the specifications above.
- 3. Colours may vary slightly from dye lot to dye lot.
- 4. Backing or other materials may be changed without prior notice when shortages occur or when technological advancements become available which provide for improvement of the product's performance.
- 5. All products are 100% recyclable.

